



APPROX. 1/4" CLEARANCE
BETWEEN EA. CORNER
AND EDGE OF COLLAR

POURABLE
SEALANT AS SPEC.

NON-SHRINK
GROUT AS SPEC.

1" MIN.
PIPE DIAMETER

OPTIONAL: WOOD
NAILERS; VARIES
DEPENDING UPON
SIZE OF PENETRATION

SEALANT AS SPEC.

DRAW BAND

WATERTIGHT 24 GA. METAL
RAIN COLLAR OVERLAPPING
PENETRATION POCKET

SHEET METAL PITCH PAN,
SOLDERED/WELDED WATERTIGHT
(4" MIN. HEIGHT)

ROOF CEMENT OR SEALANT AT
PENETRATION TO MEMBRANE
JUNCTURE

4" MIN. FLANGE,
SET IN ROOF CEMENT OVER
BUILT-UP ROOFING PLYS,
PRIME FLANGE BEFORE
STRIPPING

FLEX CTR 150 FLASHING

PLYSHEET FLASHING
AS SPECIFIED

FLEX CTR 150 BLACK

FLEX PLY SHEET/BASE SHEET
AS SPEC.

FLEX RECOVER BOARD

THERMAL INSULATION AS SPEC.

FLEX BASE SHEET (OPTIONAL)

EXISTING / NEW ROOF DECK

NOTE:

THIS DETAIL DEPICTS CUSTOM FABRICATED CONSTRUCTION. MANY MANUFACTURERS NOW OFFER PRE-FABRICATED FLASHING PIECES OR PERMIT THE USE OF MATERIALS FOR FLASHING PURPOSES OTHER THAN THOSE THAT ARE SHOWN HERE. SPECIFICS ON THESE PROPRIETARY DESIGNS VARY GREATLY, AND INDIVIDUAL MANUFACTURERS' SPECIFICATIONS SHOULD BE CONSULTED FOR THEIR USE.

TITLE	Pitch Pan	
Name	Detail No. CTR-605	
Drawn By:	JA	Reviewed BY: KF
Applicable to all Flex CTR Roof Systems		
FLEX MEMBRANE INTERNATIONAL	2670 Leiscz's Bridge Rd. Leesport, PA 19533 800-969-0108 www.flexmembranes.com	