

FILL PAN WITH FLEX POURABLE SEALER OVER CONCRETE

2" HEAT WELD

PREFORMED FLEX OUTSIDE CORNER (REQ'D) ON ALL CORNERS

FLEX PVC FLASHING MEMBRANE

RIVET CORNER PIECES

FLEXCLAD METAL (REQ'D)

6 IN. MIN.

3 1/2 IN. MIN.

DUCT TAPE

FLEX PVC FIELD MEMBRANE

FASTENERS 6" O.C.

FLEX TRIM STRIP

INSULATION SECURELY FASTENED OR ADHERED

SEPERATION LAYER WHERE REQUIRED

DECK OR EXISTING BUR

POURABLE SEALER IS A MAINTENANCE ITEM, MAINTENANCE ITEMS ARE NOT INCLUDED UNDER THE FLEX WARRANTY.

TITLE	FLEXCLAD PITCH PAN		
NAME	DETAIL NO. 4.90		
DRAWN BY:	KF	DATE:	10/2009
APPLICABLE TO ALL FLEX PVC			
MECHANICALLY FASTENED SYSTEMS			
FLEX MEMBRANE INTERNATIONAL	2670 LEISCZ'S BRDIGE RD. LEESPORT, PA 19533 800-969-0108 FlexRoofingSystems.com		