



FLEX LA432M
LOW VOC ELVALOY® AND PVC MEMBRANE BONDING ADHESIVE

PRODUCT DESCRIPTION

Flex LA432M is a contact-type bonding adhesive specially designed for bonding Elvaloy® and PVC single ply roofing membranes and flashings to horizontal and vertical substrates. Flex LA432M has been engineered to provide ultimate bonding strength and to meet all VOC restrictions and regulations in the United States.

FEATURES AND BENEFITS

- Low VOC <250g/L
- Extremely high initial tack
- Fast drying solvent system
- Easy application using roller or brush
- Excellent green strength
- High peel and shear values
- Excellent heat resistance

FLAMMABILITY Red Label ó EXTREMELY FLAMMABLE

APPLICATION

1. Use only after careful consideration of the warnings, directions, and first aid instructions given.
2. Apply adhesive when ambient temperature is 40°F (4.4°C) and rising.
3. Stir the adhesive vigorously by hand to achieve a homogeneous mixture prior to application. DO NOT use electrical equipment or open flame near the adhesive.
4. Apply adhesive to the membrane and substrate surfaces which are clean, dry and free of debris. Apply at the rate of approximately 120 square feet per gallon per surface, sufficient to bond 60 square feet of membrane in place. The coverage rate will vary depending on the porosity of the substrate surface.
5. Apply adhesive using a 3/8" medium nap solvent resistant roller.
6. Allow adhesive to partially dry to a tacky feel when touched with the back side of a dry finger before bonding membrane to substrate (approximately 5-10 minutes). Open time prior to mating membrane to substrate may extend up to 60 minutes.
7. Mate the membrane to the substrate avoiding any air entrapment, and apply pressure by means of a push broom or roller to assure complete bonding.

NOTE: The shelf life for an unopened container of this adhesive, stored at temperatures between 60°F (15.5 °C) and 80 °F (26.7 °C) out of direct sunlight, is 1 year from date of manufacture

PHYSICAL PROPERTIES

Base:	Synthetic polymer	Total Solids:	24% +/- 1%
Solvent:	Ketone blend	Voc Content:	199.4 grams/liter
Flash Point:	<0°F (-18°C)	Shelf Life:	1 year, unopened
Weight/Gallon:	7.08lbs	Open Time:	Up to 60 minutes
Color:	Natural	Dry Time:	5-10 minutes
Viscosity:	1,800-2,400 cps	Application:	Roller or brush
Coverage:	60 sq. ft/gallon bonded		

CAUTION

- Keep out of reach of children
- Product for professional or industrial use only
- Sale to consumer is in violation of federal law
- Do not use if you cannot read, or do not understand all directions, cautions and warnings.
- See MSDS for More Information

Flex Membrane International maintains Material Safety Data Sheets on all of its products. Material Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers.

Flex's Material Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Flex products in your facilities.

ATTENTION: Empty container may still contain pressure and remains hazardous until all flammable vapors, which may explode upon ignition, are gone from residue and container. Observe all labeled hazard precautions. Do not cut, puncture, or weld while hazard exists. Dispose of according to all federal, state, and local regulations.

Notice To Purchaser: NO WARRANTIES, EXPRESS OR IMPLIED ARE MADE INCLUDING MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL FLEX MEMBRANE INTERNATIONAL CORP BE LIABLE FOR ANY LOSS OR DAMAGE ARISING FROM THE PURCHASE, USE, OR INABILITY TO USE THIS PRODUCT, OR FOR ANY SPECIAL, INDIRECT INCIDENTAL, OR CONSEQUENTIAL DAMAGES. THE USER MAY SEND A SAMPLE OF PRODUCT TO FLEX FOR TESTING. IF SUCH TESTING PROVES A PRODUCT DEFECT, THE USER'S SOLE AND EXCLUSIVE REMEDY IS EITHER REIMBURSEMENT OF THE PURCHASE PRICE OF THE PRODUCT OR REPLACEMENT OF THE CONTAINER OF PRODUCT. NO FABRICATOR, INSTALLER, DEALER, AGENT OR EMPLOYEE OF FLEX HAS THE AUTHORITY TO MODIFY THE OBLIGATIONS OR LIMITATION OF THIS WARRANTY. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state; therefore, some of the limitations stated above may not apply to you. It is to your benefit to save your documentation of purchase of a product.

Please direct all inquiries regarding performance of this product to:
Flex Membrane International Corp.
2670 Leiszø Bridge Road
Suite 400
Leesport, PA 19533
Phone: 800-969-0108 Fax: 610-916-9501

Elvaloy® is a registered trademark of DuPont.