

OlyBond500[®]

GREEN ADHESIVE FASTENER



It is easy being green.

OlyBond500 Green provides all the ease and performance of OlyBond500 while satisfying important environmental considerations.

- Plant-based formula uses rapidly renewable resources in its composition
- VOC and odor free
- Contributes to LEED[®]-certified projects
- Carries same FM approvals as OlyBond500
- Environmentally sensitive packaging
- Available for both **Bag-in-Box** and **SpotShot** applications

Flex[™]

Thermoplastic Single Ply and Multi-Ply Roofing Systems

800-969-0108 • 610-916-9501 (Fax)
2670 Leisz's Bridge Road, Suite 400, Leesport, PA 19533
e-mail: flexroof@cs.com • www.flexroofingsystems.com



**Specify GREEN today...
for tomorrow.**

Not Just Environmentally Friendly – User Friendly, Too

OlyBond500 Green is a dual-component polyurethane adhesive that can be easily applied using our innovative PaceCart dispenser or lightweight SpotShot applicator. Since it is plant-based and both odor and VOC free, OlyBond500 Green is the ideal choice for LEED-specified projects.



Uses

OlyBond500 Green can be used to adhere a variety of insulation and cover boards to a wide selection of roof substrates in both new and re-roof applications. It is also an excellent choice for adhering multiple layers of insulation board and cover board. For more details, refer to Application and Technical Data Sheets.

Application

OlyBond500 Green is dispensed in a semi-liquid band that spreads to several inches before rising 3/4"–1" above the substrate. The insulation/cover board is placed into the adhesive and walked into place. A chemical cure takes place in approximately 4 to 8 minutes after application.

Product Data

OlyBond500 GREEN

PRODUCT CODE	DESCRIPTION	UOM	WT/ BOX	QTY/ SKID	COVERAGE (12" O.C.)*
6056	Part 1 Green	ea	51.6 lb	32	1–2 sq/gal
6056	Part 2 Green Regular Formula 60°–90°F	ea	42.7 lb	32	1–2 sq/gal
6056	Part 2 Green Summer Formula 90°F +	ea	42.7 lb	32	1–2 sq/gal
6056	Part 2 Green Winter Formula 40°–60°F	ea	42.7 lb	32	1–2 sq/gal

OlyBond500 GREEN SpotShot

PRODUCT CODE	DESCRIPTION	UOM	WT/ CASE	QTY/ SKID	COVERAGE (12" O.C.)*
6058	Green SpotShot Regular Formula 40°F +	ea	19 lb	40	4–6 sq/case

*Coverage rate varies depending on substrate and application. Refer to Application and Technical Data Sheets for details.

Flex™

Thermoplastic Single Ply and Multi-Ply Roofing Systems

800-969-0108 • 610-916-9501 (Fax)
2670 Leisz's Bridge Road, Suite 400, Leesport, PA 19533
e-mail: flexroof@cs.com • www.flexroofingsystems.com

