



FLEX SA PRIMER

PRODUCT DESCRIPTION

Flex SA Primer is an SBS polymer based primer for use in approved multi-ply membrane and flashing assemblies. Flex SA Primer is comprised of a proprietary blend of SBS polymers, solvents and additives used to increase adhesion when using Flex SA Vapor Barrier membrane. Flex SA Primer may be applied to gypsum, metal, wood and masonry substrates.

APPLICATION

Mix prior to application. Flex SA Primer is applied to the approved area via brush, roller, or spray equipment. Flex SA Primer is applied at a rate of 0.7 to 1 gallon per 100 square feet over non porous substrates. Refer to Flex Roofing application manual for additional application guidelines.

QUICK FACTS

5 gal. (18.9 L) Pails - Coverage Rate 0.7:1 gallon /100 ft² (0.3:0.4 L/m²)

PRODUCT INFORMATION

Description - proprietary blend of synthetic polymers, solvents

Installation - brush or roller

Packaging - 5 gallon (18.9 L) pail

Pails Per Pallet - 36

STORAGE

Store in pail and maintain in an upright position to prevent damage. Store in a clean dry location and cover as necessary to protect pails from environmental damage such as extreme cold, heat, or moisture. Monitor varying environmental conditions during storage, handling and application of Flex SA Primer.

LIMITED WARRANTY

The manufacturer believes the information and recommendations herein to be accurate and reliable. However, since use conditions are not within its control, the manufacturer does not guarantee results from use of such products or other information herein and disclaims all liability from any resulting damage or loss. **No warranty, express or implied, is given as to the merchantability, fitness for particular purpose, or otherwise with respect to the products referred to.**