



FLEX RS FLEECE

PRODUCT DESCRIPTION

Flex RS Fleece is a proprietary weave polyester reinforcement used in Flex RS liquid membrane applications. Flex RS Fleece is approved for use in Flex PVC roofing and waterproofing flashing applications.

APPLICATION

Mix and apply Flex RS liquid products in strict accordance with published instructions. Apply mixed resin liberally to the prepared surface with a brush, roller or notched squeegee. Roll out Flex RS Fleece into the liquid resin, making sure that the roll is unrolling smooth and without any wrinkles or fish mouths. Flex RS Fleece will begin to saturate into the liquid resin. Using a roller, wet the fleece with resin, applying light pressure. Roll the fleece with a nap roller to eliminate any air bubbles, wrinkles, etc. Apply additional liquid resin mix on top of Flex RS Fleece until fully saturated and the layer of resin is fully and evenly applied. The coat should be uniform. See published specifications and approved details.

PACKAGING

Flex RS Fleece is available in rolls 164 ft. (50 m) in length and varying widths. See fleece dimensions chart for more information.

STORAGE

Always store in a dry location protected against the elements. Store on end to avoid deforming rolls and creasing fabric.

PHYSICAL PROPERTIES

Thickness	30-40 mils (0.8-1.0 mm)
Weight	110 g/m ²
Tensile strength at break. MD/XD	≥ 130/150
Elongation	≥ 50/70
Tear Resistance	20 > daN
Puncture Resistance	24 >daN
Water Absorption	< 1 %

FLEECE DIMENSIONS

13.8 in. (35 cm) x 164 ft. (50 m)	10.3 in. (26 cm) x 164 ft. (50 m)
41.3 in. (105 cm) x 164 ft. (50 m)	20.7 in. (53 cm) x 164 ft. (50 m)