



NOTE:
WHEN SELVEDGE EDGE OCCURS ON FASCIA SIDE OF
NAILER, NAIL THROUGH THE FLEECE BACK OF THE
MEMBRANE ONLY.

EXPOSED FACE DIMENSION GREATER THAN 3" REQUIRES
A CONTINUOUS CLEAT SAME GAUGE AS FACE METAL.

- CONTINUOUS CLEAT NOT SHOWN FOR CLARITY.

FLEX CLAD METAL IS CUT FROM FULL SIZE SHEETS
AND FORMED BY CONTRACTOR TO ANY OF THE SMACNA
APPROVED PERIMETER METAL PROFILES USED IN LOW
SLOPE ROOF INSTALLATIONS.

FLEX CUT EDGE SEALANT IS REQUIRED ON ALL NON
FACTORY CUT EDGES

TITLE	
FLEXCLAD PERIMETER EDGE METAL	
NAME:	
DETAIL NO. 1.30	
DRAWN BY:	DATE:
SK	6/2014
APPLICABLE TO ALL FLEX	
TPO ROOFING SYSTEMS	
FLEX MEMBRANE INTERNATIONAL	2670 LEISCZ'S BRIDGE RD. LEESPORT, PA 19533 800-969-0108 FlexRoofingSystems.com