



NOTE:
 WHEN SELVEDGE EDGE OCCURS ON FASCIA SIDE OF
 NAILER, NAIL THROUGH THE FLEECE BACK OF THE
 MEMBRANE ONLY.

EXPOSED FACE DIMENSION GREATER THAN 3" REQUIRES A CONTINUOUS
 CLEAT SAME GAUGE AS FACE METAL.

- CONTINUOUS CLEAT NOT SHOWN FOR CLARITY.

FLEX CLAD METAL IS CUT FROM FULL SIZE SHEETS AND FORMED BY
 CONTRACTOR TO ANY OF THE SMACNA APPROVED PERIMETER METAL
 PROFILES USED IN LOW SLOPE ROOF INSTALLATIONS.

FLEX TPO: FLEX TPO CUT EDGE SEALANT IS
 REQUIRED ON ALL NON FACTORY CUT EDGES OF FLEX
 TPO

TITLE FLEXCLAD SPILL OUT SCUPPER	
NAME: DETAIL NO. 1.80	
DRAWN BY: SK	DATE: 11/2017
APPLICABLE TO ALL FLEX	
ADHERED ROOFING SYSTEMS	
FLEX MEMBRANE INTERNATIONAL	2670 LEISCZ'S BRIDGE RD. LEESPORT, PA 19533 800-969-0108 FlexRoofingSystems.com