

OlyBond

NightShot

TEMPORARY TIE-IN

Fast acting, dual-component, low-rise polyurethane foam forms a temporary seal between new roof covers and existing roof systems.

Temporarily seals TPO, EPDM, and PVC to Built-up and Modified Bitumen roof systems.

FAST. SAFE. EASY.

Application

- Dispense through a portable 1:1 applicator.
- Apply in a single band on the old roof surface at the intersection of the new roof system. Roof surface must be clean, dry, and free of all loose gravel and dirt.
- Allow NightShot to rise before pressing the new roof membrane into the foam. Ensure that new membrane is in full contact with NightShot; do not allow voids or fishmouths along edge.
- Cut away contaminated membrane and NightShot before continuing with new roof application.
- Keep NightShot at room temperature; do not apply when the deck temperature is below 40°F.
- NightShot is not a substitute for fasteners, and will not resist wind uplift forces. Membrane must be held in place with temporary ballast.

FlexTM

Thermoplastic Single Ply and Multi-Ply Roofing Systems

5103A Pottsville Pike, Reading, PA 19605
Phone: 610-916-9500 Fax: 610-916-9501
www.FlexRoofingSystems.com



Coverage

- Each cartridge covers approximately 50–100 linear feet of tie-in.

Storage

- Store upright, at room temperature, and keep from freezing. Each case contains four (4) 1500ml cartridges.