



NOTE:
 WHEN SELVEDGE EDGE OCCURS ON FASCIA SIDE OF NAILER, NAIL THROUGH THE FLEECE BACK OF THE MEMBRANE ONLY.

EXPOSED FACE DIMENSION GREATER THAN 3" REQUIRES A CONTINUOUS CLEAT SAME GAUGE AS FACE METAL.

- CONTINUOUS CLEAT NOT SHOWN FOR CLARITY.

FLEX CLAD METAL IS CUT FROM FULL SIZE SHEETS AND FORMED BY CONTRACTOR TO ANY OF THE SMACNA APPROVED PERIMETER METAL PROFILES USED IN LOW SLOPE ROOF INSTALLATIONS.

FLEX TPO: FLEX TPO CUT EDGE SEALANT IS REQUIRED ON ALL NON FACTORY CUT EDGES OF FLEX TPO

TITLE	
FLEXCLAD PERIMETER EDGE METAL	
NAME:	
DETAIL NO. 1.10	
DRAWN BY:	DATE:
SK	8/2019
APPLICABLE TO ALL FLEX	
ADHERED ROOFING SYSTEMS	
FLEX MEMBRANE INTERNATIONAL	2670 LEISCZ'S BRIDGE RD. LEESPORT, PA 19533 800-969-0108 FlexRoofingSystems.com