



# Product Data Sheet

## FLEX PIPE FLANGE

### PRODUCT DESCRIPTION

The Flex Pipe Flange is prefabricated for quick and easy flashing installations. The Flex Pipe Flange can be cut to fit various dimensions of 1" to 4 1/2" in diameter. The Flex Pipe Flange is installed by the hot air welding method. The Flex Pipe Flange facilitates labor savings and ensures a quality installation.

### PHYSICAL PROPERTIES

<u>Property</u>	<u>Test Procedure</u>	<u>Specification</u>
Color		White, Gray or Tan
Size		7" in height / fits diameters up to 4 1/2"
Thickness	ASTM D638	.085" Nominal
Specific Gravity	ASTM D792	1.32g/cm <sup>3</sup>
Tensile Strength	ASTM D638	>2500 PSI
Elongation	ASTM D638	>300
Heat Aging	ASTM D3045	90% of Original
Cold Resistance	ASTM D1043	-40 Degrees F
Water Vapor Permeability	ASTM E96	2.8g/m <sup>2</sup> /day
Dimensional Stability	ASTM D1240	0.5% or less
U.V. Stability	Xenon Arc 150	10,000 hrs. (Excellent)

\*All Flex Pipe Flange applications require the included metal clamp to be installed at the top of preformed flange and sealed with an approved caulking applied.