



FLEX TPO WALKWAY PAD

PRODUCT DESCRIPTION

Flex TPO Walkway Pad is a thermoplastic walkway pad designed to provide protection to Flex TPO Roof Membrane in those areas exposed to repetitive foot traffic and other hazards.

APPLICATIONS

Walkway pads are installed at traffic concentration points such as roof hatches, access ladders, doors and mechanical equipment service areas.

BENEFITS

Flex TPO Walkway Pads are hot air welded directly to the TPO roof membrane for a permanent installation.

Tread pattern is slip resistant.

INSTALLATION

Membrane is prepared for walkway installation by cleaning with Flex Weathered Membrane Cleaner. Walkway pad is cut into 10’ maximum lengths and positioned with a 2” gap between sections to allow for water drainage. Do not cover the field seams in the TPO roof membrane. All four edges of the walkway pad are hot air welded to the TPO roof membrane.

LIMITATIONS

Do not install walkway pads within 10’ of the roof perimeter.

Walkway pads are considered auxiliary components and are not covered under the Flex Membrane roof warranty.

PHYSICAL PROPERTIES

Roll Size		34” x 50’
Weight		88 lbs.
Color		white, tan, gray
Membrane Thickness		180 mil total
Density	ASTM D792	80.5 lb/ft ³
Tensile Strength	ASTM D638	600 psi
Tear Strength	ASTM D624	100 lbf/in